

PORTABLE EYEWASH

This product can be used in field of Petroleum, Chemical, Laboratory, Medical Treatment etc., and flushing the chemistry liquid splattered eye and face rapidly, reduce the level of injury to the minimum.

Pull down eye wash arm placidly, so open to spray.

When wash eyes, open eyes wholly, sufficient wash, the wash time is not less than 15 minutes.

After wash, need medical treatment forward.

- ◆ Material: Polyester, pro-environment and safety.
- ◆ Water injection hole: Wide water injection hole and apt to inject water, have dust cover.
- ◆ Water flow: Due to change diameter on the water hole, so more bonhomie and enrich, water yield is not lower than 1.5L/minute.



16 Gallon capacity

H7501



8 Gallon capacity

H7500

EMERGENCY SHOWER AND EYE WASH STATION

This product is safety device for emergency treatment in hazardous work areas and laboratories in pharmaceutical, chemical, petrochemical, electronics, and semiconductor companies.

◆ The main material is stainless steel, with high-brightness epoxy resin surface coating, which is anti-corrosion, anti-ultraviolet radiation and anti-leak.

◆ The spray and eye wash is controlled through ball valve and spiral sealing structure, which is convenient for operation, fast open and close and reliable sealing.



ZYES02-S



ZYES03-A



ZYES05-S



ZYES06-S



ZYES-H01



ZYES31-1080

MODEL	ZYES01-S	ZYES02-S	ZYES03-A	ZYES04-A	ZYES05-S	ZYES06-S	ZYES-H01	ZYES31-1080
Product name	Compound emergency shower	Compound emergency shower	Compound emergency shower	Compound emergency shower	Vertical eyewash	Wall mounted eyewash	Electric heating compound eye wash station	Emergency shower & eyewash room
External Dimension L*W*H mm	800x400x2340	800x400x2340	800x400x2340	800x400x2340	360x330x1050	400x380x280	800x400x2452	900x1000x2400
Main material	Stainless steel 304	Stainless steel 304	Stainless steel 304 ABS coated	Stainless steel 304 ABS coated	Stainless steel 304	Stainless steel 304	Stainless steel 304 ABS coated	Stainless steel 304
Water inlet and outlet	DN32	DN32	DN32	DN32	DN32	DN32	DN32	DN32
Eyewashing flow L/min	12-18	12-18	12-18	12-18	12-18	12-18	11.4	12-18
Sprinkler spacing mm	101.6	101.6	101.6	101.6	101.6	101.6	101.6	101.6
Foot pedal	without	with	without	with	with	without	without	with
Water pressure Mpa	0.25-0.4	0.25-0.4	0.25-0.4	0.25-0.4	0.25-0.4	0.25-0.4	/	0.25-0.4