



EU-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.



Certificate N° 0075/4650/162/10/22/1906

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : TAICANG QIHUA KNITWEAR CO.,LTD
999 Yinxi South Road, Shaxi Town, Taicang City, Suzhou, Jiangsu Province, China
CHINA

Description

PPE Type : *protective glove against mechanical risks*

Product reference : PE-108

Article code : /

Glove description : 13 gauge HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex shell gloves with sandy nitrile coated palm

Available sizes : 6/XS - 12/XXXL

Pictures :

LOT



999 Yinxi South Road, Shaxi Town, Taicang City, Suzhou, Jiangsu Province, China



HONORSAFE
好员工

EN388:2016
+A1:2018



PE-108

4X42F

9/L

Reference standard :

Levels of performance / class of protection

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

EN ISO 21420:2020

-

EN 388:2016 + A1:2018

4 X 4 2 F

At the date of the certificate, the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from OCTOBER 2022

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

Issued in Lyon by
Nadine PIPAZ
CE Expert Team Coordinator



Date of first issue : 31 October 2022

End of validity date : 31 October 2027

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir: Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726



TAICANG QIHUA KNITWEAR CO.,LTD

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	PE-108
Article code	:	/
Technical file index	:	01
Last update	:	OCTOBER 2022

IDENTIFICATION

Reference of the product :	:	PE-108
Article code :	:	/
Basic Model		
Technical file index :	:	01
Last update :	:	OCTOBER 2022

Manufacturer :

TAICANG QIHUA KNITWEAR CO.,LTD

999 Yinxi South Road, Shaxi Town,Taicang City,Suzhou,Jiangsu Province,China

CHINA

tel : 0512-53229380

fax : 0512-53233500

Factory :

TAICANG QIHUA KNITWEAR CO.,LTD

999 Yinxi South Road, Shaxi Town,Taicang City,Suzhou,Jiangsu Province,China

CHINA

tel: 0512-53229380

fax: 0512-53233500

GLOVE DESCRIPTION

General glove description and intended use:

13 gauge HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex shell gloves with sandy nitrile coated palm

This glove is designed against mechanical risks.

Type of coating finish : sandy

Visual description (picture back and palm sides) :



Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	☒	☒ Standard ☒ Instruction for use ☒ Marking
§1.4	Manufacturer's instructions and information is available	☒	☒ Standard ☒ Instruction for use ☐ Marking
§2.5	PPE which may be caught up during use	☒	☐ Standard ☒ Instruction for use ☐ Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	☒	☒ Standard ☒ Instruction for use ☒ Marking
§3.3	The PPE is intended to protect against mechanical injuries	☒	☒ Standard ☒ Instruction for use ☒ Marking

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		black	nitrile			0.5mm
		black/white	HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex	260g/m ²	13G	
Back		black/white	HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex	260g/m ²	13G	
Cuff		black/white	HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex/ elastic	280g/m ²	13G	
Binding		grey/brown	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN ISO 21420 : 2020

Dexterity : 5

Available size range: 6/XS - 12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B table B.1

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	X
Tear strength resistance	4
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	F
Impact Protection	-

The levels of performance have been measured on the palm.

TEST REPORTS

Laboratory	CTC	Other
EN ISO 21420 + innocuousness	S220805121_1 S220805151_1 S220100300_1	
EN 388	S220805121_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : PE-108

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or serial/batch number :

Date of obsolescence (month/year) if applicable:

Marking example :



Method of marking on the glove :

printing on the back

Packaging suitable for transport:

12 pairs in the transparent poly bag, 12 dozens in a carton

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Cleaning instructions:

The gloves are not washable.

MEANS OF CONTROL

Firstly, IQC will take sample to monitor (ISO 2859, G1) the knitting gloves performance. They check the gloves on hand former, and monitor the glove color, total length, weight, visual defect Ext. If find abnormal will follow the non-conforming procedure to handle it.

Then, IPQC will check the product after dipping, they will check the total length, palm width, weight, and monitor the visual defects and performance, example: taste, dipping position Ext.

The next is packing process, QA will monitor the logo, bag, carton, label Ext. If ok, the glove will be send to warehouse.

In warehouse, FQC will check the final product.

This is a strict monitor procedure. We pick out the defects around 2%-4% in this process. We can ensure the quality according it.

Then, we will ship the gloves to our customer site.

When we beginning a new order, we will test the gloves firstly. The testing includes abrasion(test every one year), cut, tear, puncture,TDM CUT.

For EN ISO 21420 test, we asked our vendor to according to the request, and they cannot use any materials which contain Hazardous Substances. For each style, we send the final gloves to third party to monitor it for no more than 3 years.



INSTRUCTION FOR USE

TAICANG QIHUA KNITWEAR CO.,LTD

999 Yinxi South Road, Shaxi Town, Taicang City, Suzhou, Jiangsu Province, China
CHINA

Glove reference : PE-108
Article code: /
User notice index : 01
Last update : OCTOBER 2022

HONORSAFE
好员工

EN388:2016
+A1:2018



PE-108 4X42F 9/L

Glove description :

13 gauge HPPE (high performance polyethylene)/ glass fiber/ nylon/ spandex shell gloves with sandy nitrile coated palm

This glove is a personal protective equipment belonging to the category II.

It meets the requirements of the PPE Regulation 2016/425 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE



999 Yinxi South Road, Shaxi Town, Taicang City, Suzhou, Jiangsu Province, China

Applicable standards :

The glove meets the requirements of the standard EN ISO 21420:2020 « Protective Gloves - General requirements and test methods ».

Dexterity: 5

Available size range: 6/XS - 12/XXXL

The hand sizing system is based on hand circumference and hand length as defined in EN ISO 21420 Annex B.

Moreover, this glove has been designed for the following applications :

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

« 0 » indicates that the glove falls below the minimum performance level for the individual hazard.

Application :

Mechanical hazard - EN
388:2016 + A1:2018



Read carefully the instructions for use provided with the product



4 X 4 2 F

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	X	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	F	(A to F)
Impact Protection		

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

Before use, the glove shall be visually inspected for any defect or imperfections. In case of deterioration, the gloves must be scrapped (abrasion, cut, tear, ...).

No flame protection is claimed. This glove shall not be in contact with naked flame.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

The levels of performance against mechanical risks are only valid for the palm of the glove.

For dulling during the cut resistance test, the coupe test results are only indicative while the TDM cut resistance test is the reference performance result.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The gloves are not washable.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.