P200 - FFP2 Respirator (Pk20)

Collection: Disposable Mask FFP2
Range: Disposable Masks
Materials: PP, EVA Foam
Inner Pack: 20
Outer Carton: 16



Product information

Comfortable cup style respirator. Protects against fine toxic dust, fumes and water based mists. The respirator can be used in concentrations of contaminants up to 10 times the WEL.

Disposable Mask FFP2

Disposable mask FFP2 level, protects against solid and liquid particles of average toxicity. Minimal % of filtration 94%. Protects up to 10 times the TLV (Assigned Protection Factor for FFP2 masks). Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics /cutting, deburring, grinding, drilling of metal. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex® brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex® range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex® range includes disposable masks and limited-life garments.

Standards

AS/NZS 1716 (P2)
NIOSH N95
EN 149:2001 +A1:2009 FFP2 (NR)

Features

- Adjustable nose bar for improved fit and reduced fogging of glasses
- Ultrasonic welded head straps
- Foam padding around the nose bridge for additional comfort
- Comfortable cup style respirator
- Retail box which aids presentation for retail sales
- CE certified
- UKCA marked
- CE-CAT III

P200 - FFP2 Respirator (Pk20)
Commodity Code: 6307909311

Test House
BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
John M. Keynesplein 9
, The Netherlands
Cert No: CE 714896

BSI Assurance UK Ltd (Notified Body No.: AB: 0086)
The British Standards Institution
MK5 8PP, United Kingdom
Cert No: UKCA 758904

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m^3)	EAN13	DUN14
P200WHR	White	52.0	29.0	36.0	0.3220	0.0543	5036108159994	15036108635792