PRODUCT SPECIFICATION & TECHNICAL DATA

P261 - Trifold Valved Dolomite FFP2 Respirator (Pk10)

Collection: Disposable Mask FFP2
Range: Disposable Masks
Materials: Spunblown Polypropylene, Meltblown Polypropylene, Mono PU, Aluminium, Elastic
Outer Carton: 16



Product information

Flexible trifold design adapts to a variety of different face shapes. Soft nose foam for a secure and comfortable fit. Packed inside individual polybags for hygienic storage and is vending machine ready. Dolomite clogging tested.

Disposable Mask FFP2

Disposable mask FFP2 level, protects against solid and liquid particles of average toxicity. Minimal % of filtration 94%. Protects up to 10 times the TLV (Assigned Protection Factor for FFP2 masks). Examples of applications: Sanding of soft wood, composite materials, rust, putty, plaster, plastics /cutting, deburring, grinding, drilling of metal. Our Biztex brand ensures exceptional quality and performance across our full range of disposable masks.

Disposable Masks

Our Biztex® brand ensures exceptional quality and performance across our full range of disposable masks. The extensive Biztex® range offers a high level of protection and quality safeguarding the wearer against many workplace risks including liquid chemicals, static electricity, dry particles and radioactive contamination. The complete Biztex® range includes disposable masks and limited-life garments.

Standards

EN 149:2001 +A1:2009 FFP2 (NR D)

Features

- Flexible shape which allows the mask to be folded flat
- High performance exhalation valve to reduce heat and provide comfort when used in hot and humid conditions
- Adjustable nose bar for improved fit and reduced fogging of glasses
- Foam padding around the nose bridge for additional comfort
- Dolomite optional clogging test (D) to provide more comfortable breathing and longer lasting filtration performance
- 100% Metal Free
- Individually packed for vending machines
- Retail box which aids presentation for retail sales
- CE certified
- CE-CAT III
- New style

PRODUCT SPECIFICATION & TECHNICAL DATA

P261 - Trifold Valved Dolomite FFP2 Respirator (Pk10)
Commodity Code: 6307909311

Test House
BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
John M. Keynesplein 9
, The Netherlands
Cert No: 714896

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m^3)	EAN13	DUN14
P261WHR	White	43.0	37.0	33.0	0.2120	0.0525	5036108434824	15036108921673